Getac

Windows 10

Getac recommends Windows 10 Pro for business



UX10 FULLY RUGGED TABLET

- 10th Generation Intel® Core™ i7/i5 Processor
- 10.1'' FHD LumiBond® 2.0 Display with Getac Sunlight Readable Technology (1,000 nits) and Capacitive Touchscreen
- Enhanced Enterprise Security with Optional Intel vPro™, Windows Hello Face-authentication Camera and Multi-factor Authentication Options
- Detachable Keyboard and Multifunctional Hard Handle for On-the-job Flexibility
- Multiple Configurable Options to Fit Diverse Usage Scenarios

CERTIFIED MIL-STD 810H

CERTIFIED MIL-STD 461G

INGRESS PROTECTION IP65


6' Drop



Detachable Keyboard



Hard Handle



Rugged Mobile Computing Solutions

Specifications

Operating System
Windows 10 Pro

Mobile Computing Platform
Platform Options:

Intel® Core™ i7 Technology
Intel® Core™ i7-10510U Processor 1.80 GHz
8MB Intel® Smart Cache

Intel® Core™ i7 vPro™ Technology
Intel® Core™ i7-10610U Processor 1.80 GHz vPro
8MB Intel® Smart Cache

Intel® Core™ i5 Technology
Intel® Core™ i5-10210U Processor 1.60 GHz
6 MB Smart Cache

Intel® Core™ i5 vPro™ Technology
Intel® Core™ i5-10310U Processor 1.70 GHz vPro
6MB Intel® Smart Cache

VGA Controller
Intel® UHD Graphics

Display
10.1" IPS TFT LCD FHD (1920 x 1200)
1000 nits LumiBond® display with Getac sunlight readable technology
Capacitive multi-touch screen

Storage & Memory
8GB DDR4
Optional: 16GB / 32GB DDR4

256GB PCIe NVMe SSD
Optional: 512GB / 1TB PCIe NVMe SSD

Keyboard
6 tablet buttons (Windows, Power, Function Key, Camera Capture/ Barcode Reader Trigger, Volume Up, Volume Down)

Pointing Device
Touchscreen
- Capacitive multi-touch screen
- Optional: Dual mode touchscreen (multi-touch and digitizer)

Expansion Slot
- Optional (top side): 1D/2D imager barcode reader[i], or serial port, or MicroSD slot, or USB 3.0 Type-A port, or USB 3.1 Gen 1 Type-C port, or LAN port (RJ-45), or VGA port[ii], or HF RFID reader.
- Optional (right side): fingerprint reader, or serial port+LAN port (RJ-45), or HF RFID reader[iv].
- Optional (back side): smart card reader, or bridge battery, or bridge battery+smart card reader[v]

I/O Interface
FHD webcam x 1 or Optional Windows Hello face-authentication camera (front-facing) x 1
8M pixels auto focus rear camera x 1
Headphone out / mic-in combo x 1
DC in Jack x 1
USB 3.1 Gen 2 Type-A x 1
HDMI x 1
Docking connector x 1
Optional: RF antenna pass-through for GPS, WLAN and WWAN

Communication Interface
Optional: 10/100/1000 base-T Ethernet
Intel® Wi-Fi 6 AX200, 802.11ax
Bluetooth (v5.1)[vi]
Optional: Dedicated GPS[iii]
Optional: 4G LTE mobile broadband with integrated GPS[iii]

Security Feature
Optional: Intel® vPro™ Technology
TPM 2.0
Optional: HF RFID reader[i,ii]
Optional: Fingerprint scanner[iv]
Optional: smart card reader[iv]
Kensington lock

Power
AC adapter (65W, 100-240VAC, 50 / 60Hz)
Li-Ion smart battery (11.1V, typical 4200mAh; min.4080mAh) x 1
Optional: High capacity battery (10.8V, 9240mAh) x 1
Optional: Bridge battery[v]

Dimension (W x D x H) & Weight
276.8 x 194.5 x 23.5 mm (10.89" x 7.65" x 0.92"), 1.22 kg (2.68 lbs)[vii]

Rugged Feature
MIL-STD-810H certified and IP65 certified
MIL-STD-461G certified[viii]
Optional: ANSI/UL 121201, CSA C22.2 NO. 213
Optional: Salt fog certified
6 feet drop resistant[ix,x]
e-Mark certified for vehicle usage

Environmental Specification
Temperature[x]:
- Operating: -29°C to 63°C / -20°F to 145°F
- Storage: -51°C to 71°C / -60°F to 160°F

Humidity:
- 95% RH , non-condensing

Software
Getac Utility
Getac Camera
Getac Geolocation
Getac Barcode Manager
Optional Absolute Persistence

Accessories
Carry bag
Multi-bay charger (Dual Bay)
Multi-Bay charger (Eight-Bay)
Vehicle adapter (120W, 11-32VDC)
AC adapter (65W, 100-240VAC)
Offie dock AC adapter (90W, 100-240VAC)
MIL-STD-461 certified AC adapter (90W, 100-240VAC)
Digitizer pen
Capacitive stylus (Hard-tip)
Protection film
Tablet folio case
Hand strap
Shoulder harness (4-point; handsfree)
Shoulder strap (2-point)
Standard battery (11.1V, typical 4200mAh; min. 4080mAh)
High capacity battery (10.8V, 9240 mAh)
Detachable keyboard
Vehicle dock
Office dock

Bumper-to-Bumper warranty
Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime.

That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs.

Bumper-to-Bumper is your hassle-free guarantee.

That means you can depend on us to have your unit back in service within days.

Standard
3 years Bumper-to-Bumper

---

i 13.56MHz Contactless HF RFID reader (ISO 15693, 14443 A/B, Mifare and FeliCa™ compliant).
ii 1D/2D imager barcode reader, HF RFID reader, serial port, LAN port (RJ45), USB 3.0 port, USB 3.1 Gen 1 Type-C port, MicroSD slot and VGA port are mutually exclusive options.
iii Supports GPS and Glonass.
iv Fingerprint scanner, HF RFID reader and serial port+LAN port (RJ45) are mutually exclusive options.
v Smart card reader, bridge battery and bridge battery+smart card reader are mutually exclusive options.
vi Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
vii Weight and dimensions vary from configurations and optional accessories.
viii MIL-STD-461G 90W AC adapter sold separately.
ix Drop test results vary from configurations and optional accessories.
x Tested by a national independent third party test lab following MIL-STD-810H.

UX10
Fully Rugged **Tablet**



Docking Solutions

	Vehicle Dock	*Office Dock*
Serial Port	1	1
VGA	--	1
Microphone	--	1
Audio Output	--	1
DC in Jack	1	1
USB	USB 3.0 x2 USB 2.0 x2	USB 3.0 x2 USB 2.0 x2
LAN	1	1
HDMI	--	1
RF Antenna Connector	3 (WWAN, WLAN, GPS)	--
Kensington Lock	1	1

Getac

GETAC TECHNOLOGY CORPORATION
5F, Building A, No. 209, Section 1, Nangang Rd.,
Nangang Dist., Taipei City, 11568, Taiwan, R.O.C.
Tel : +886 2 2785 7888
globalmarketing@getac.com | www.getac.com

Copyright © 2020 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved.
Information provided herewith is for reference only,
available specification shall be subjected to quotation by request. V01M08Y20WW